

# Product data sheet - Pluggit GmbH

## Ventilation unit AD160 with clock control

Ventilation unit AD160 - basic version

Supplier	Pluggit GmbH		
Model identifier	<b>AD160</b>		
SEC [kWh/(m <sup>2</sup> *a)] for each climate zone (cold, average, warm)	-78.9	-39.1	-13.7
SEC class	A+	<b>A</b>	E
Type	Domestic ventilation unit; bi-directional ventilation unit		
Type of drive	Multi-speed drive		
Type of heat recovery system	Recuperative		
Thermal efficiency of heat recovery [%]	94.1		
Maximum flow rate [m <sup>3</sup> /h]	180		
Electric power input of fan drive	127		
Sound power level (Lw(A))	49		
Reference airflow	0.035 [m <sup>3</sup> /s] 126 [m <sup>3</sup> /h]		
Reference pressure difference [Pa]	50		
SPI [W/m <sup>3</sup> /h]	0.27		
Ventilation control (clock control, no demand control)	0.95		
Internal and external leakage [%]	Internal: 0.5 External: 0.7		
Position/type of filter indicator/filter change frequency	Comfort keypad; remote control/ flashing LED/1x p.a.		
Website	www.pluggit.com		
Annual electricity consumption per 100 m <sup>2</sup> (AEC) [kWh/a] for each climate zone (cold, average, warm)	887	350	305
Annual heating energy savings (AHS) [kWh prim./a] for each climate zone (cold, average, warm)	92.4	47.2	21.4

